

FIBRE CEMENT Touch Up Paint

Keeping the exterior of your home looking brand new all year round can be challenging with harsh weather conditions, the environment, and other factors causing chips and knocks on your Fibre Cement Wall Cladding.

Cladco Fibre Cement Touch Up Paint is available in all seven matching Fibre Cement Colours to ensure that any imperfections that may occur over time can be covered. Our Touch Up Paint is a water-based solution designed to re-touch, cover surface damage or paint over any cut ends on Cladco Fibre Cement Wall Cladding Boards, keeping your home's exterior Cladding looking seamless all year round and improving the finish as and when required.

Cladco Fibre Cement Touch Up Paint is designed for retouching small areas of Cladco Fibre Cement Boards only, it is not recommended for large areas.



Advantages of Fibre Cement Touch Up Paint

- Available in all seven matching Fibre Cement colours
- Use only on surface damage/ imperfections/ends of Boards
- Water-based formula
- Smooth, even finish
- Provides excellent coverage and colour retention



HANDLING & STORAGE

Warning. Avoid contact with eyes. Use safety glasses with side shields – wash with water if contact is made and seek medical assistance if irritation continues. Avoid contact with skin. Use neoprene gloves when handling – wash affected skin with soap and water. Do not swallow - wash hands after use and in case of ingestion, drink plenty of water and seek immediate medical assistance. Avoid inhalation of the product. Use in a well-ventilated area to avoid breathing in fumes – move to fresh air and seek medical assistance if irritation occurs. Where ventilation is poor, provide CE-marked RPE appropriate to the air contaminants. Keep out of reach of children - keep container fully closed and store in temperatures between 10°C and 35°C.

SPECIFICATIONS	
Size	500ml
Weight	0.69kg

COLOURS



PLEASE NOTE – You may receive a 1-litre container of paint as opposed to a 500ml container when ordering. Only for use on Cladco Fibre Cement Wall Cladding Boards and is not for use on Fibre Cement Wall Cladding from other manufacturers.

**Please note, this paint product has possible health and safety hazards. Please refer to the container for full health and safety information.

T: 01837 659 901 E: info@cladco.co.uk

WWW.CLADCODECKING.CO.UK

Beardown Road, Exeter Road Industrial Estate, Okehampton EX20 1UA

MATERIAL SAFETY Data Sheet



SECTION 1: HAZARDS IDENTIFICATION

Classification of the product: No need for classification for this product in accordance with **General rule for classification and hazard communication of chemicals**

SECTION 2: COMPOSITION/ INFORMATION ON INGREDIENTS

This product is chemical mixture and does not contain any substances presenting a health or environmental hazard.

CHEMICAL NAME	CAS NUMBER	CONCENTRATION
Acrylic ester copolymer	/	46-48%
H ₂ O	7732-18-5	52-54%
5-Chloro-2-methyl-3(2H)-isothiazolone	26172-55-4	≤22.5ppm
mixt.with 2 methyl 3(2H) isothiazolone	2682-20-4	≤7.5ppm

SECTION 3: FIRST AID MEASURES

Inhalation:	Move into fresh air
Skin contact:	Wash affected areas thoroughly with soap and water. If skin irritation persists, seek medical attention.
Eye contact:	Rinse with plenty of water for at least 15 minutes. If eye irritation persists, seek medical attention.
Ingestion:	Flush at once and then drink copious amounts of water, seek medical attention if necessary. Do not give anything by mouth to an unconscious victim.

SECTION 4: FIRE FIGHTING MEASURES

Suitable media:	Use extinguishing media appropriate for surrounding fire
Special hazard arising during fire fighting:	When temperature is above 100°C/212°F, material will splatter and may burn after it is dried.
Advice for fire fighters:	Wear self contained breathing apparatus and protective clothing.

MATERIAL SAFETY

Data Sheet



SECTION 5: ACCIDENTAL RELEASE MEASURES

Personal precautions:	Personal protective equipment should be used. People should be kept away from or upwind of spill/leak. In addition, material may create slippery condition.
Environmental precautions:	Do not allow the spills and waste to reach sewage or effluent systems pick up with suitable absorbent material (e.g. sand, soil)
For small amount:	Pump off product.
For large amount:	Spill should be transferred to suitable container for recovery or disposal.
Methods for cleaning up:	Dispose of material in accordance with local regulations.

SECTION 6: HANDLING AND STORAGE

Handling:	Avoid contact with eyes. Skin and clothing. Wash thoroughly after handling. Keep container tightly closed. Do not breathe vapor, mist or gas.
Storage temperature:	10°C-35°C
Further information:	Store away from freezing as product stability may be affected. Please stir well before use.
Other data:	Monomer vapors can be evolved when material is heated during processing operations and several types of ventilation are required (see section 8).

SECTION 7: EXPOSURE CONTROLS/ PERSONAL PROTECTION

Eye protection:	Safety glasses with side shields. Eye protection worn must be compatible with respiratory protection system employed.
Hand protection:	The gloves listed below may provide protection against permeation: Neoprene gloves (Gloves of other chemically resistant materials may not provide adequate protection).
Respiratory protection:	Use certified respiratory protection equipment, when respiratory risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods or procedures of work organization.
Engineering measures:	Use only in area provided with appropriate exhaust ventilation.

MATERIAL SAFETY Data Sheet



SECTION 8: PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Liquid		
Odor:	Acrylic odor		
Boiling point: (water)	100°C		
Lower explosion limit:	Not applicable		
Vapor Pressure: (water)	17mmHg 20°C	Colour:	Milky white & bluish
Water solubility:	Dilatable	PH:	7±1
Viscosity, dynamic:	200-2000cps	Flash point:	Noncombustible
Percent volatility:	53±1%	Upper explosion limit:	Not applicable
MFFT:	23°C	Relative vapor density:	<1.00 (water)
Relative density	Wet: 1.0_1.1	Particle Diameter:	0.1-0.2µm
Proportion:	Dry: 1.1-1.2	Evaporation rate:	< 1.00 (air=1)
		Latex style:	Anionic

NOTE: The physical data presented above are typical values and should not be construed as a specification.

SECTION 9: STABILITY AND REACTIVITY

Hazardous reactions:	No hazardous reactions have been reported.
Materials to avoid:	There are no known materials that are incompatible with this product.
Polymerization	Product will not undergo polymerization
Decomposer:	Acrylic monomer can produced by thermal decomposition

MATERIAL SAFETY Data Sheet



SECTION 10: TOXICOLOGICAL INFORMATION

No data are available for this material. This information shown is based on profiles of compositionally similar materials.

Acute oral intoxication: Half lethal does (LD50)>5,000 mg/kg (rat)

Acute skin toxicity: Half lethal does (LD50)>5,000 mg /kg (rabbit)

Skin irritation: May lead to short term irritation (rabbit)

Eyes irritation: Nonirritating (rabbit)

Respiratory intoxication: Half lethal does (LD50)>21 mg/l (rat)

SECTION 11: ECOLOGICAL INFORMATION

No data is available for this product.

SECTION 12: DISPOSAL CONSIDERATIONS

Environmental precautions: Keep spills and cleaning waste out of sewage, surface waters or effluent systems.

Disposal: Coagulate the emulsion by stepwise addition of ferric chloride and lime. Remove the clear supernatant and flush to a chemical sewer. For disposal, incinerate or landfill at a permitted facility in accordance with local regulations.

SECTION 13: TRANSPORT INFORMATION

Road and Rail transport: Not regulated (not dangerous for transport)

Sea transport: Not regulated (not dangerous for transport)

Air transport: Not regulated (not dangerous for transport)

Notice: Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations.

MATERIAL SAFETY

Data Sheet



SECTION 14: REGULATORY INFORMATION

General rule for classification and hazard communication of chemicals (GB 13690 2009)

Classification has been performed according to regulations.

General rules for precautionary label for industrial chemicals (GB 15258 2009)

Label has been performed according to regulation.

Inventory of Existing Chemical Substances in China (IECSC)

All intentional components are listed on the inventory, are exempt, or are supplier certified.

Toxic Substances Control Act (TSCA)

All components of this product are in compliance with the inventory listing requirements of the Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

SECTION 15: OTHER INFORMATION

Reference:

Safety data sheet for chemical products Content and order of sections (GB 16483 2008)

Notice:

The information provided in this Safety Data Sheet in accordance with the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.