

3.6M WOODGRAIN COMPOSITE BULLNOSE BOARD

PRODECK RANGE



*In accordance with our installation guide, the ProDeck boards have 20-year warranty when installed with Cladco recycled plastic joists


This 3.6m woodgrain effect ProDeck bullnose board is designed to create a clean, rounded edge, ideal for steps, borders, and finishing details. Made with the same durable, polymer-capped woodgrain finish as our ProDeck decking boards, it's available in seven colour options for a seamless match.

COLOUR RANGE



BOARD SPECIFICATIONS		
Length	3.6m	
Width	150mm	
Thickness	23mm	
Weight	14.47kg (approx)	

TEST CERTIFICATIONS		
FSC® Ce	ertification	SA-COC-005542
SKU	Burnt Oak Onyx Platinum Pewter Rosewood Sandstone	WPCEB36B WPCEP36B WPCEPE36B WPCER36B WPCES36B




Please Note: Images are for illustration purposes only. Actual products may vary slightly from those shown.











SURFACES

The capped surface provides increased strength and resistance against the elements.



ACCESSORIES

Can be used alongside our ProRange composite fascia boards to complete your decking area.



LOW MAINTENANCE

ProDeck composite boards do not need to be sealed, stained or varnished and are easy to clean.



WARRANTY

These ProDeck bullnose composite boards have a 20-year warranty when installed with our recycled plastic joists.

RECYCLED MATERIALS

Cladco ProDeck bullnose boards have a core made from 100% recycled materials. The composite core is a mix of 60% recycled hardwood fibres and 40% recycled post-consumer plastics to help reduce our environmental impact.

Our ProDeck range takes our composite decking core and caps it with a polymer protective shell to increase the board's resilience. The subsequent decking board is more resistant to weather conditions, scratching, staining and fading due to UV rays.

All Cladco composite products are available as FSC® certified for the same cost. If you require FSC® certified products, please ask for these when placing your order.

AFTERCARE

Cladco ProDeck bullnose composite decking boards may naturally accumulate dirt over time due to outdoor conditions. For everyday debris such as plants, leaves, berries or animal droppings, simply brush your decking with a broom.

In cases of more stubborn dirt or grime, using warm soapy water may be necessary to restore the decking's appearance.



INSTALLATION ADVICE


Bullnose Finish

Please note that bullnose boards are intended for use as borders around your capped composite decking area. Due to natural batch variations and the timber within the boards, they are not designed to blend seamlessly with the rest of your capped composite decking. For an enhanced aesthetic, we recommend choosing a contrasting colour to create a picture frame effect.

Number of Screws

Fit the ProDeck board over the starter/bullnose clips and push forward until flush. They can then be secured in place with T-clips as required before continuing to install the rest of your standard ProDeck boards.





Adhering to these guidelines will help ensure proper installation and longevity of your capped composite decking. Failure to follow these guidelines will invalidate the product's warranty.

TEMPERATURE EXPANSION

The capped shell surface of the composite core means that the boards are less likely to be effected by temperature changes. It means that the boards are more resistant to expansion or retraction due to heat and cold, making it a very stable option.

The polymer shell also provides protection against weather conditions and increased insulating properties. This improved thermal performance helps regulate indoor temperatures and reduce heating and cooling costs.

For detailed information about installation, please read our ProDeck decking installation guide.

PRODUCT ACCESSORIES



PRODECK DECKING BOARDS



PRORANGE COMPOSITE CORNER TRIM



PRORANGE COMPOSITE FASCIA BOARDS



RECYCLED PLASTIC BATTENS



COMPOSITE BATTENS

